

GATE TENDER NOTICE
BENGAL CHEMICALS & PHARMACEUTICALS LTD.
164, Maniktala Main Road,
Kolkata: 700054

Dated: 27.12.2016

Sealed tender are invited from bonafide resourceful and experienced contractor, for the work of civil repairing work in existing tablet & ointment section BCPL, Maniktala factory.


BOQ for civil repairing work in existing tablet & ointment section BCPL, Maniktala factory.


sl	particulars of items	unit	Qty	Rate	Amount
1	Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade : Old work (one or more coats)	sqm	2250		
2	Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq. meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground within 50 metres lead : With cement mortar 1:4 (1 cement : 4 fine sand)	sqm	130		
3	Renewing glass panes, with putty and nails wherever necessary including racking out the old putty: Float glass panes of thickness 4 mm	sqm	10		
4	Demolishing wall plusher in cement mortar including stacking material within 50metres lead	sqm	150		
5	Providing and fixing aluminium extruded section body tubular type universal hydraulic door closer (having brand logo with ISI, IS : 3564, embossed on the body, door weight up to 36 kg to 80 kg and door width from 701 mm to 1000 mm), with double speed adjustment with necessary accessories and screws etc. complete.	each	15		
6	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade : One or more coats on old work	sqm	200		
7	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	sqm	300		
8	Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level. Cement mortar 1:4 (1 cement :4 coarse sand)	sqm	5.5		
9	12 mm cement plaster of mix : 1:4 (1 cement: 4 fine sand)	sqm	10		
10	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge. Internal work - Exposed on wall 50 mm nominal outer dia Pipes	metre	4		


11	Providing and fixing false ceiling at all height including providing and fixing of frame work made of special sections, power pressed from M.S. sheets and galvanized with zinc coating of 120 gm/sqm (both side inclusive) as per IS : 277 and consisting of angle cleats of size 25 mm wide x 1.6 mm thick with flanges of 27 mm and 37mm, at 1200 mm centre to centre, one flange fixed to the ceiling with dash fastener 12.5 mm dia x 50mm long with 6mm dia bolts, other flange of cleat fixed to the angle hangers of 25x10x0.50 mm of required length with nuts & bolts of required size and other end of angle hanger fixed with intermediate G.I. channels 45x15x0.9 mm running at the spacing of 1200 mm centre to centre, to which the ceiling section 0.5 mm thick bottom wedge of 80 mm with tapered flanges of 26 mm each having lips of 10.5 mm, at 450 mm centre to centre, shall be fixed in a direction perpendicular to G.I. intermediate channel with connecting clips made out of 2.64 mm dia x 230 mm long G.I. wire at every junction, including fixing perimeter channels 0.5 mm thick 27 mm high having flanges of 20 mm and 30 mm long, the perimeter of ceiling fixed to wall/partition with the help of rawl plugs at 450 mm centre, with 25mm long dry wall screws @ 230 mm interval, including fixing of gypsum board to ceiling section and perimeter channel with the help of dry wall screws of size 3.5 x 25 mm at 230 mm c/c, including jointing and finishing to a flush finish of tapered and square edges of the board with recommended jointing compound, jointing tapes, finishing with jointing compound in 3 layers covering upto 150 mm on both sides of joint and two coats of primer suitable for board, all as per manufacturer's specification and also including the cost of making openings for light fittings, grills, diffusers, cutouts made with frame of perimeter channels suitably fixed, all complete as per drawings, specification and direction of the Engineer in Charge but excluding the cost of painting with 12.5 mm thick tapered edge gypsum plain board conforming to IS: 2095- Part I	sqm	100		
12	Applying bounding cota on RCC/CC / Brick work for receiving cement concrete/ cement mortar using cement slurry 1.50kg / Sqm admixing with polymer modified cementitious adhesive [Sika Latex power or equivalent] as per manufacture specification i/c rounghening, cleaning etc. complete	sqm	100		
TOTAL					


- (i) Detailed price breakup to be given by the parties in their quotation.
(ii) Parties are requested to inspect the site before submitting the offer.
(iii) Payment will be made on submission of bill after successful completion of the job.

The tender should be addressed to the **Works Manager**, BCPL, 164, Maniktala Main Road, Kolkata-700054 & to be submitted on or before 02.01.2017 at 3:00 pm. and opening of the quotations will be in the same dated at 3:30p.m.


27/12/16
Civil Engineer


27/12/16
Mgr (P&E)


27/12/16
AGM (Q.A)


27.12.16
WMM